



Commercial Grade LED T8 Lamp

Flex™
Internal Driver LED Lamp

Features & Benefits

- Assembled in USA
- Internal Driver
- Smooth, Consistent Light
- UL for Safety
- No UV, No Mercury
- Long Life
- High CRI
- Instant on, no delay or warm up time
- Convenient and quick installation
- Utilizes G5 sockets
- Compatible with controls and sensors
- Works in cold temperature applications
- 5 Year Warranty
- High performance plastic series



Specification Data

Model No.	Length	Base type	Lamp Wattage	Input Voltage	CCT	Initial Lumens	CRI	Beam Angle	LPW	Power Factor	THD	DLC
L24T5/830/7G-ID DE TAA	24	G5	7	120-277	3000K	900	82	240	128	0.9	<20%	No
L24T5/835/7G-ID DE TAA	24	G5	7	120-277	3500K	900	82	240	128	0.9	<20%	No
L24T5/840/7G-ID DE TAA	24	G5	7	120-277	4000K	900	82	240	128	0.9	<20%	No
L24T5/850/7G-ID DE TAA	24	G5	7	120-277	5000K	900	82	240	128	0.9	<20%	No

Ordering Information

EXAMPLE: **L48T8/840/14G-ID DE**

L	48	T8	8	40	12 P	-	ID	DE
Manufacturer's Code	Normal Length 48=48"	Lamp Shape T8=T8	CRI 8=>80	CCT 50=5000K 40=4000K 35=3500K	Wattage 12P-12W		Internal Driver	Double End Input

Wiring diagram

