

Linear T5HE/HO

L48T5HO/8XX/24G-EB

Commercial Grade LED T5 Lamp



Descriptions:

The RetroFlex (Type A) LED lamps provide hassle-free installation with simple lamp-for-lamp replacements for your linear fluorescent T5HE or T5HO retrofit needs. Fully certified to replace original fluorescent lamps, these lamps provide the perfect, hassle-free solution for whatever the project requires. When being used with an instant start, programmed start, or emergency backup ballast, no fixture re-wiring is needed.







Features & Benefits:

- No rewiring needed
- Works with fluorescent electronic T5 ballast
- Long life
- High CRI
- Instant on, no delay
- Convenient and quick installation
- Utilizes existing T5 sockets
- Compatible with controls and sensors
- No Mercury, No UV
- Works in cold temperature applications
- Full Glass Design
- Super Wide View Angle, 240
- 5 Year Warranty






Specifications:

| Ordering Code | Length (in) | Lamp Wattage | System Wattage | CCT (K) | Initial Lumens | CRI | Beam Angle | Lamp Efficacy | System Efficacy | Life (hr) |
|--------------------|----------------|-----------------|-------------------|------------|-------------------|-----|---------------|------------------|--------------------|--------------|
| L48T5HO/830/24G-EB | 48 in | 24W | 27W | 3000K | 3100 | 83 | 240 | 129 | 115 | 50000 |
| L48T5HO/835/24G-EB | 48 in | 24W | 27W | 3500K | 3100 | 83 | 240 | 129 | 115 | 50000 |
| L48T5HO/840/24G-EB | 48 in | 24W | 27W | 4000K | 3200 | 83 | 240 | 133 | 118 | 50000 |
| L48T5HO/850/24G-EB | 48 in | 24W | 27W | 5000K | 3200 | 83 | 240 | 133 | 118 | 50000 |

Wiring Diagram:



DLC Listing:

| Ordering Code | DLC Product ID | DLC Product Model | DLC Version |
|--------------------|----------------|-------------------------|-------------|
| L48T5HO/830/24G-EB | PLWIPVXQGYNW | L48T5HO/830/24G-EB(-aa) | 5.1 |
| L48T5HO/835/24G-EB | PLYVSXVM5FPY | L48T5HO/835/24G-EB(-aa) | 5.1 |
| L48T5HO/840/24G-EB | PLTCO057BNCL | L48T5HO/840/24G-EB(-aa) | 5.1 |
| L48T5HO/850/24G-EB | PLSIQWFR2301 | L48T5HO/850/24G-EB(-aa) | 5.1 |

- Please refer to "Ballast Compatibility List" for compatible battery backup and/or emergency ballasts.
- Please refer to "Ballast Compatibility List" on Related Downloads.

Specification data is based on tests performed in a controlled environment and represents relative performance. Actual performance can vary depending on operating conditions. Application and performance data subject to change without notice. All specifications are nominal unless noted otherwise.

