



**Commercial Recessed Downlight
BAA/TAA Compliant**

Features & Benefits

- 1 Commercial Downlight Retrofit or New Construction
- Universal Voltage 120-277V
- UL for Safety, Wet-Location Rated
- Three Adjustable Lumen Output
- Three Adjustable CCT Options (3000K, 3500K, 4000K)
- High CRI
- Long Life
- Convenient and quick installation
- 0-10V Dimmable
- 25" Flexible Conduit
- Works in cold temperature applications
- Flicker-free, Meets IEEE 1798-2015
- 5 Year Warranty



Specification Data

Model No.	Size	IC Rated	Watts	Lumens	CCT	Efficacy	Input Voltage	CRI	Power Factor	Dimension
VEKR4D/9T/14W-10V TAA	4" Recess	Yes	6 / 9 / 14	470 / 700 / 950	3000K, 3500K, 4000K selectable	79 / 77 / 73	120-277	90	0.9	Dia. 5.71" x Height 3.70"

Ordering Information

Sample model: VEKR4D/9T/14W-10V BAA

VEKR	4D	9T	14W	10V	BAA
Series Retrofit Kit Recessed Light	Size 4" Downlight	CRI>90 T: three CCT adjustable	Wattage 14W Max.	Dimming 0-10V	COO BAA TAA



User Manual

[468inDownlightInstallation.pdf](#)