



**Commercial Recessed Downlight**  
BAA/TAA Compliant

### Features & Benefits

- Commercial Downlight Retrofit or New Construction
- Universal Voltage 120-277V
- UL for Safety, Wet-Location Rated
- Three Adjustable Lumen Output
- Three Adjustable CCT Options (3000K, 3500K, 4000K)
- High CRI
- Long Life
- Convenient and quick installation
- 0-10V Dimmable
- 25" Flexible Conduit
- Works in cold temperature applications
- Flicker-free, Meets IEEE 1798-2015
- 5 Year Warranty



### Specification Data

Model No.	Size	IC Rated	Watts	Lumens	CCT	Efficacy	Input Voltage	CRI	Power Factor	Dimension
VEKR9.5D/8T/27W-10V TAA	9" Recess	Yes	17 / 21 / 27	2070 / 2500 / 3240	3000K, 3500K, 4000K selectable	120	120-277	>80	0.9	Dia. 11.22" x Height 5.04"

### Ordering Information

Sample model: VEKR4D/8T/10W-10V BAA

VEKR	4D	8T	10W	10V	BAA
Series	Size	CRI>80	Wattage	Dimming	COO
Retrofit Kit	4"	T: three CCT adjustable	10W Max.	0-10V	BAA
Recessed Light	Downlight				TAA



User Manual

[9.5inDownlightInstallation.pdf](#)